

## PIPE EQUIPMENT SPECIALISTS LTD

## PREP 8 PIPE BEVELLING 2" to 8"















Portable Pipe Bevelling Machine

## RANGE: 50 to 207mm i/d

Functions: External Bevelling

Internal Bevelling Elbow Bevelling

**Facing** 

Counter-boring Weld Removal J-Prepping

**Compound Bevels** 

Materials: Any kind of Steel

and Exotic Alloy

Power: Pneumatic / Electric

(110v or 220v)

One of our most powerful and popular i/d locking, in-line feed end prep machines. This is mainly due to its impressive 2 - 8" working range and unrivalled power.

The PREP 8 is a portable, one man operation machine, its power to weight ratio, and offset 4 jaw tool holder (chuck) allows use of up to 4 insert or form tools to enables simultaneous external, internal bevelling of even the heaviest wall pipe.

The PREP 8 is a real workhorse. It's size, power, and functionality, make it extremely popular in high volume heavy duty bevelling applications, on site, or in the fabshop.



The PREP 8 is torque reactive. This means that the pipe or tube does not have to be fixed to be bevelled, making it particularly useful on-site, in maintenance and repair situations. This is due to the design and strength of the thru shaft system that locks to the bore of the pipe.

The Jaw system itself consists of 3 equilaterally positioned machined jaw segments, retained and locked on an inner, 'grooved' expansion shaft.

These grooves keep the jaws held securely in position, unlike other systems that use a metal or rubber bands for jaw retention.

As the expansion nut is tightened, the jaws expand, locking tightly, and square to the bore of the pipe.









## **POWER OPTIONS:**







## **ACCESSORIES & OPTIONS:**







PART NO. TP8AHK






## PREP 8 TECHNICAL FEATURES:

DESCRIPTION	MEASUREMENT	PNEUMATIC	ELECTRIC
Part Number	-	TP8P	TP8E
Locking tube range	mm (i/d.)	50 - 207	50 - 207
Recommended working range	inch (o/d.)	2" - 8"	2" - 8"
Idle speed	rpm	0 - 52	5 - 34
Torque	kgm/nm	36 / 353+	45 / 441+
Length of axial feed	mm	40	40
Max operating temperature	c°	55	55
Max acoustic radiation	dB	75	75
Pneumatic motor power	hp	1.8	-
Air consumption	cfm	44 - 50	-
Air working pressure	psi	90	-
Air hose connection	inches	3/4"	-
Electric motor power	watt	-	1700
Voltage	volt	-	110 / 220
Frequency	Hz	-	50 / 60
Unit weight	kg	25	26
Packing dimensions	mm	880 x 640 x 240	880 x 640 x 240
Packing weight	kg	53	54

# All units are supplied complete with all locking jaws to cover the full range of the machine. Service tools, drawings, instruction manual and warranty certificate and protective metal carrying case.

## **DIMENSIONS** C В D Ε DIM **PNEUMATIC ELECTRIC** Α 670mm 700mm В 520mm 520mm 278mm С 278mm D 220mm 220mm Ε 86mm 90mm







## PIPE EQUIPMENT SPECIALISTS LTD PRODUCTS INCLUDE:

## PIPE BEVELLING MACHINES

















## **TAG Head Office**

TAG PIPE EQUIPMENT SPECIALISTS LTD
Unit 15 & 16 Grendon Industrial Estate, Grendon Underwood,
Aylesbury, Buckinghamshire, HP18 OQX England
Tel: +44 (0)1869 324 144 E-mail: sales@tag-pipe.com

www.TAG-PIPE.com

## **Overseas Branches**



## **USA** Branch

TAG PIPE EQUIPMENT SPECIALISTS INC 527 Michigan Street, South Houston Houston, Texas 77587, USA Tel: +1 713 660 1427 E-mail: sales-usa@tag-pipe.com



## **Europe Branch**

TAG PIPE EQUIPMENT SPECIALISTS BVBA
Mosten 13, 9160 Lokeren
Belgium
Tel: +32 486 46 62 93

E-mail: sales-europe@tag-pipe.com



## Middle East Branch

TAG PIPE EQUIPMENT SPECIALISTS FZE
Al Ittihad Street, P.O. Box 3763
Dubai, United Arab Emirates
Tel: +971 (0)50 680 3107
E-mail: sales-me@tag-pipe.com



## India Branch

TAG PIPE EQUIPMENT SPECIALISTS PVT
Plot No. PAP 3, D 3 Block,
Chinchwad, Pune 411 019
Tel: +91 20 6573 4333
E-mail: sales-india@tae-pipe.com



## Asia Branch

TAG PIPE EQUIPMENT SPECIALISTS PTE
Yinhe Bridge West, Beichen District
Tianjin, China
Tel: +86 139 2001 5417
E-mail: sales-asia@tae-pipe.com